

DRAWINGS:

Insert corrected drawings Figs. 1-28 submitted in duplicate herewith

5

CLAIMS

Amend claims 1-17 as follows:

1.(Amended) A guide (30) for a crib comprising:

a base with a first slot (44)formed in said base with said first slot (44)having a periphery, a second slot (38) formed in said base and a third slot (40)formed in said base communicating with said first and said second slots, with said base having an outer edge;

a first spring (42) mounted on said base and disposed blocking said second slot (38)

2. (Amended) The guide (30) for a crib of claim 1 in which said first spring (42) comprises:

a cantilever spring having a first end mounted on said base and a second end.

3. (Amended) The guide (30) for a crib of claim 2 further comprising:

a recess portion (54) formed in said base disposed to receive said second end of said first spring.

4. (Amended) The guide (30) for a crib of claim 2 further comprising:
a step portion (52) formed on said second end of said first spring (42).

5. (Amended) The guide (30) for a crib of claim 4 further comprising:
a wall (62) disposed proximate said step portion (52).

6. (Amended) The guide (30) for a crib of claim 1 further comprising a ramp
portion (46) formed in said second slot (38).

7. (Amended) The guide (30) for a crib of claim 1 further comprising:
a T-shaped slot (72) communicating between said first slot (44) and said
outer edge.

8. (Amended) The guide (30) for a crib of claim 7 further comprising:
a second spring (80) projecting from said base and comprising an end
disposed projecting into said T-shaped slot (72).

9. (Amended) The guide (30) for a crib of claim 7 further comprising:
an aperture portion (90) formed in said base, disposed proximate and in
general alignment with said end (82) of said second spring (80).

10. (Amended) A crib (10) comprising:

headboard(26),
a side rail (16),
an elongated upper guide (24),
sliding means (20) mounted on said side rail for engagement of
said upper guide;

a lower guide (30) comprising:

a base with a first slot (44) formed in said base with said first slot
having a periphery, a second slot (38) formed in said base and a third slot (40)
formed in said base communicating with said first and said second slots, with
said base having an outer edge;

a first cantilever spring (42) disposed projecting from said base
and disposed blocking said second slot with said cantilever spring having a tip.

11. (Amended) The crib of claim 10 further comprising:

a least one pin (68) projecting from said base of said lower guide (30) and
disposed engaging said headboard.

12. (Amended) The crib of claim 10 in which said sliding means mounted on
said side rail comprises:

a pin (20) projecting from said side rail and engaging said elongated upper
guide.

13. (Amended) The crib of claim 10 in which said sliding means mounted on said side rail (16) comprises:

a pair of flanges (106) (108) with said flanges engaging said elongated upper guide (102).

14. (Amended) The guide (30) for a crib of claim 2 in which said first spring (42) comprises:

a metal cantilever spring.

15. (Amended) The guide (30) for a crib of claim 2 in which said first spring (42) comprises:

a plastic cantilever spring.

16. (Amended) The guide (30) for a crib of claim 1 in which said guide spring (42) comprises:

a plastic member.

17. (Amended) The guide for a crib of claim 2 in which said first spring (42) comprises:

a leaf spring (318).
